armacell

Declaration of Performance No. 0551-CPR-2015-015

Unique identification code of the product-type:

Intended use/es:

Manufacturer:

System/s of AVCP:

NH/Armaflex

Thermal insulation of building equipment and industrial installations (ThiBEII)

Armacell Poland Sp.zo.o. UI. Targowa 2 PL-55-300 Środa Śląska

3

EN 14304:2009+A1:2013

NB 0919

Harmonised standard:

Notified body/ies:

Declared performance/s:

Essential characteristics	Performance		
Thermal resistance / Thermal conductivity	tubes	d _№ = 9-25mm	$λ_{0^{\circ}C} ≤ 0,040 W/(m^{*}K),$ $λ(ϑ_m) = (40 + 0,1 ⋅ ϑ_m + 0,0009 ⋅ ϑ_m^2) / 1000$
Reaction to fire	tubes	d _N = 9-25 mm	D _L -s2,d0
Durability of thermal resistance against ageing/degradation	Dimensional stability ¹⁾ Minimum service temperature ST(-)-50 (= -50 °C)		
Durability of thermal resistance against high temperature	Maximum service temperature ST(+)110 (=110 °C)		
Durability of reaction to fire against ageing/degradation	Durability characteristics ²⁾		
Durability of reaction to fire against high temperature	Durability characteristics ²⁾		
Water permeability	NPD		
Water vapour permeability / Water vapour diffusion resistance	tubes	d _N = 9-25 mm	Mu 2000 (µ ≥ 2000)
Rate of release of corrosive substances	Trace quantities of water-soluble chloride ions CL80 (≤80 ppm)		
Acoustic absorption index	NPD		
Release of dangerous substances to indoor environment	NPD ³⁾		

This declaration of performance is made available in accordance with Article 7(3) of Regulation (EU) No 305/2011 on our homepage: <u>www.armacell.com/DoP</u>.



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer indentified above.

Signed for and on behalf of the manufacturer by: Malte Witt, General Manager EU South at Sroda Slaska on 01.12.2015

[signature]