

TECHNICAL DATA SHEET GLASS CLOTH TAPE

F/R GRADE COLD WEATHER

PRODUCT DESCRIPTION:

Glass cloth backing 140 gsm combined with a high performance flame retardant cold weather solvent acrylic adhesive, protected by silicone release paper.

| | Adhesive Glass Cloth | |
|------------------|-------------------------|---|
| Backing Material | | Adhesive |
| GLASS CLOTH | | F/R GRADE COLD WEATHER SOLVENT ACRYLIC |

| Properties | Unit | Tolerance |
|---------------------|--------|------------|
| Tape Thickness | mic | 190 |
| Tensile Strength | N/25mm | ≥430 |
| Elongation at Break | % | 3% |
| Adhesion | N/25mm | ≥18 |
| Service Temperature | °C | -30 ~ +120 |

APPLICATIONS: Glass Cloth tapes are used for sealing of joints between glass cloth faced mineral wool products and sealing of joints between glass cloth facings and metal.

SHELF LIFE & STORAGE: Recommended shelf life of the product is 12 months. Jumbo or Finished Rolls on verticle position stored without direct sun contact and in room temperature of 21°C and humidity of 50%.

AVAILABLE COLOURS: White

NOTICE:

- (1) All Efes products are strictly inspected before sent to customers, but the applications might be different customers, there may exist factors which are beyond EFES's knowledge and control, so customers should check the quality of every order before apply the tape completely. If customers use the product without inspection, they must be responsible for the potential quality problems and economic loss. If the EFES product is proved to be defective, the exclusive remedy, at EFES's option, shall be to refund the purchase price of or replace the problematic product.
- (2) Customers who buy the jumbo rolls should stop the re-winding and slitting when there is any quality problem is found in the jumbo.Please contact EFES right away.If customers re-wind/cut the problematic jumbo into log/slit rolls, EFES will not response to make any indemnity.

*Different dimensions can be produced according to customer demands.

